

## enblock C12

### Electrical Characteristics

|   |                                  |
|---|----------------------------------|
| Total Energy Capacity                     | 13.1 kWh                         |
| Usable Energy Capacity <sup>1)</sup>      | 11.7 kWh                         |
| Battery Capacity                          | 252 Ah                           |
| Voltage Range                             | 42.0 to 58.8 V <sub>DC</sub>     |
| Nominal Voltage                           | 51.8 V <sub>DC</sub>             |
| Max. Charge/Discharge Current             | 119A                             |
| Peak Current <sup>2)</sup>                | 166.7A for 3 sec.                |
| Max. Charge/Discharge Power <sup>3)</sup> | 5.0kW                            |
| Peak Power <sup>2)</sup>                  | 7.0kW for 3 sec.                 |
| Peak Power for backup mode                | 11.0kW for 3 sec.                |
| Battery Pack Round-Trip Efficiency        | >95% (under specific condition)  |
| Communication Interface                   | CAN 2.0B                         |
| DC Disconnect                             | Circuit Breaker, Contactor, Fuse |

### Operating Conditions

|                                     |  |
|-------------------------------------|--|
| Installation Location               | Indoor / Outdoor (Stand / Wall-Mounted)          |
| Operating Temperature               | -10 to 50°C                                      |
| Operating Temperature (Recommended) | 15 to 30°C                                       |
| Storage Temperature                 | -30 to 60°C : ~7 days<br>-20 to 45°C : ~6 months |
| Humidity                            | 5% to 95%  |
| Altitude                            | Max. 2,000m                                      |
| Cooling Strategy                    | Natural Convection                               |

### Certification

|                                    |                            |                                     |
|------------------------------------|----------------------------|-------------------------------------|
| Safety                             | Cell                       | UL1642                              |
|                                    | Battery Pack               | CE / RCM / IEC 62619 / FCC / UL1973 |
| EMC                                | IEC61000-6-1, IEC61000-6-3 |                                     |
| Hazardous Materials Classification | Class 9                    |                                     |
| Transportation                     | UN38.3                     |                                     |
| Ingress Rating                     | IP55                       |                                     |

※ Test Conditions - Temperature 25°C, at the beginning of life

※ Total/Usable Energy is measured under specific condition from LGES(0.3CCCV/0.3CC)

1) Value for Battery Cell Only (Depth of Discharge 90%). Actual usable energy at the AC output may vary by condition, such as the inverter efficiency and temperature.

2) Peak Current excludes repeated short duration (less than 3 sec. of current pattern).

3) LGES recommends 0.3CP for maximum battery lifetime. Maximum power will vary due to temperature and SOC

### Features

enblock C12 battery pack designed for photovoltaic systems is easily adaptable energy storage solution. With parallel box, enblock C3.3/6.5/10 /12 can be “cross-connected” with each other.

※ Parallel box is an expansion kit specially designed for 48V models.

Number of expandable battery units : up to 2EA

- Emergency Power Back-up
- Easy and Flexible installation
  - : Easy to wall mount or install on floor
  - : Wide range of inverters available
- Proven Safety and 10 year warranty
- Compact size and space saving



### Mechanical Characteristics

|            |        |                    |
|------------|--------|--------------------|
| Dimensions | Width  | 452 mm (17.8")     |
|            | Height | 626 mm (24.7")     |
|            | Depth  | 227 mm ( 8.9")     |
| Weight     |        | 98.5 kg (217.2lbs) |



Tower1, 108, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea. 07335  
TEL : (82) 2-3773-1114 FAX : (82) 2-3773-7005  
<http://www.lghomebattery.com> <http://www.lgensol.com>